



ORGANIC DYESTUFFS CORPORATION

CORPORATE OFFICE

65 Valley Street
P.O. Box 14258
East Providence, RI 02914-0258

TEL: (800) 556-6785

TEL: (401) 434-3300

FAX: (401) 434-2390

TECHNICAL BULLETIN

ORCO LUBRICANT WS-NY®

Description: Water soluble lubricant for use in atmospheric and high-temperature dyeing applications. Helps prevent chafing and crack marks encountered with some synthetics and their blends. Also used in various scouring and fulling operations of wool piece goods to improve hand and drape properties.

Properties:

<i>Appearance</i> -	Clear pourable liquid
<i>Odor</i> -	Very low
<i>Ionic Charge</i> -	Nonionic
<i>Specific gravity</i> -	1.014
<i>Type (Class)</i> -	Polyalkylene Glycol

Applications: Applicable to nylon, polyester, and their respective blends with cellulose.

Procedures: *Dyeing:* High temperature or atmospheric: 1-2% owg
Orco Lubricant WS-NY
Circulate with standard chemicals.

Fulling and scouring: 0.5 - 1% **Orco Lubricant WS-NY** on weight of soap solution is sufficient.

C O L O R A N T S F O R A L L I N D U S T R I E S

BRANCH OFFICE: NORTH CAROLINA DIVISION
1015 Concord Parkway N · Concord, NC 28027
TEL: 800-783-6955
TEL: 704-786-1118
FAX 704-788-2415